

# FIMO

PREHUNG WOOD MODULES.  
FLUSH WITH ADJACENT GLASS PANES.  
CUSTOM VENEER.

## Product features



Interface directly with glass surface requiring no metal extrusions.

Floor to ceiling modules flush modules.

1. Swing door modules, coplanar on corridor and office side, include most advanced door technology:
  - Tension bars.
  - Modified engineered core.
  - Concealed adjustable hinges.
  - Magnetic latchset.
2. Blind wall modules
3. Shelving modules
4. Custom integrations (LED panels, white boards, projection screens, etc.)
5. Sliding doors

Trimmable height for varying field conditions  
Full integration with Lama wall system

## Applications

Commercial office partitions.

## Standards

Panel Thickness.	2 3/8" - 3 3/16"
Min./Max. Panel Width.	6"/5'
Max Std. Height.	10'
Sliding Door Thickness.	1 1/2"
Sliding Door Max Dim.	10'h x 5'w
Standard Trimmability.	3"
Shelving Module Standards.	7'h x 4'w
Blind Wall Module Standards.	10'h x 4'w
Est. STC.	35 - 48

## Top Tolerance

+/- 11/16" (17mm) + 5/8" (16mm) adjustment

## Bottom Tolerance

+/- 1/2" (12mm)

## Finishes

Custom Veneers

## Green Product Features

FSC certification on request.

## Standard Warranty

2 Years

## Construction

Modified Engineered Core.  
Tension Rods.  
Integrated Adjustability.  
Modified Concealed Hinges.

## Accessories

Swing Module - Blind Module - Wood Slider  
Integrated Shelving Units - Integrated AV Units

## Related Models

Lama - Riga - Seven