

LAMA

SLIM PROFILE WALL SYSTEM WITH WIDE ADJUSTABILITY.
SAME PROFILE FOR SINGLE OR DOUBLE GLAZING.
SIMPLIFIED INSTALLATION.

Product features



Lightness and enhanced light penetration.
Minimal extrusions.
Surface mounted or inset.
+/- 1" installation tolerance (total 2") for fixed glass.
1/4" adjustability tolerance for sliders.

Single or Double Glazing.
Integrated floor to ceiling pivot doors available as frameless, framed or solid wood.
Integrated sliding and pocket doors available as frameless, framed or solid wood.

Applications

Commercial office partitions.

Standards

Wall Thickness.	2 3/8"
Min./Max. Panel Width.	6"/4'
Max Standard Height.	10'
Top Profile Height.	3 3/8"
Bottom Profile Height.	1 1/2"
Top/Bottom Sliding Profile Height.	1 1/16"
Side Sliding Profile Height.	3/4"
Top/Bottom Swing Profile Height.	1 1/16"
Side Swing Profile Height.	13/16" - 1 1/16"
Est. STC.	32 sgl - 46 dbl

Tolerance

+/- 1" + 1/4" adjustment for levelling of sliding track

Finishes

Anodized aluminium.
Custom anodizations.
Modernus metal finishes.

Standard Warranty

2 Years

Green Product Features

Recycled aluminium extrusions available.
FSC certified.
Majority of materials can be sourced within 500 miles.

Glass Thickness (min/max)

9/16" (14mm) - 1/2" (12mm) - 3/8" (10mm)

Standard Joints

Polycarbonate extrusions or 3M Dual Lock

Construction

Architectural Grade Aluminium alloys
All aluminium profiles are anodized.
All profiles come with acoustic gaskets.

Accessories

Frameless Slider - Framed Riga Slider - Riga Swing
Wood Slider - Wood Swing - Blind Panels

Related Models

Fimo - Riga - Seven