

Highly customizable, Industrial look with visible screws and T-mullions. Engineered to simplify and streamline the installation process.

Product Features

- Center Loading single-glazed architectural system
- Profile-applied mullions: L-shaped with industrial style screws
- Glass-applied mullions: T-shaped or Flat, vertical and/or horizontal
- Mullions are cut on-site, no preliminary field measurements required to order
- Adjustable T-cap to eliminate field gapping and misalignments
- Door types: swing or sliding, framed, or wood
- Adaptable to any site condition
- Quick and easy installation

Dimensions

- Installation tolerance $\pm 5/8"$
- Extrusion height: $1\frac{1}{2}"$
- Extrusion width: $2\frac{3}{8}"$
- Opening height: standard max 10'-0"
- Glazing: $3/8"$ or $1/2"$, monolithic or laminated
- No floor leveling required
- T-mullion : $1" \times 3/4"$
- L-mullion : $3/4" \times 9/16"$

Finishes

- Black or grey powder-coated aluminum.
- Custom finishes available upon request

Standard Joints

- Polycarbonate extrusions or 3M Dual Lock upon request

Construction

Architectural grade aluminum alloys

Accessibility

ADA compliant door clearances, surfaces, and hardware

Acoustics

- All profiles come with acoustic gaskets
- Sound transmission class varies per glass type (Single glazed STC 34-39)

Sustainability

We care about the environment. Our products are engineered to minimize impact and maximize performance, with supporting certifications and transparency labels.