

FIMO

SYSTEM OVERVIEW



Sophisticated prehung wood door modules provide uninterrupted alignment with our LAMA demountable glass wall system

Product Features

- Floor to ceiling flush door module integrates seamlessly within a single or dual glazed LAMA system
- No visual metal connections between wood and glass
- Coplanarity of veneer and LAMA framing provides clean, contemporary aesthetic
- Advanced door technology: adjustable tension rods, engineered core, and concealed hinges
- Door types: hinged swing door

Dimensions

- Panel thickness: 2 $\frac{3}{8}$ "–3 $\frac{1}{8}$ "
- Standard module height: max 10', customizable up to 12'-0" upon request
- Standard module width: 4'-0", customizable upon request
- Installation tolerance: $\pm 1 \frac{1}{2}$ ", floor deviation under door $< \frac{1}{4}$ " for drop seal to properly function
- No floor leveling required

Finishes

Standard and custom veneers available, as well as specialty finishes to specifications

Construction

- Engineered core
- Tension rods
- Integrated adjustability
- Concealed hinges

Accessibility

ADA compliant door clearances, surfaces, and hardware.

Sustainability

We care about the environment. Our products are engineered to minimize impact and maximize performance, with supporting certifications and transparency labels, including FSC-certified wood.