

LAMA

SYSTEM OVERVIEW



An elegant glass wall system offering a slim profile, high adjustability, and simple installation

Product Features

- Minimal extrusions and parts
- Seamless transitions between single and double glazed variations
- Front set glass/coplanar
- Glazing: $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ " monolithic or laminated
- Variety of design options including door styles, hardware, glass types and applied mullions
- Door types: pivot or sliding, framed glass, frameless glass, or solid wood

Dimensions

- Frame width: single glazed $1\frac{1}{2}$ ", dual glazed $1\frac{1}{2}$ "
- Frame depth: single glazed $2\frac{3}{8}$ ", dual glazed $3\frac{1}{8}$ "
- Frame height standard max 10'-0"
- Fixed glass frame height up to 12' available with $\frac{5}{8}$ " glass (excludes doors)
- Installation tolerance ± 1 "
- No floor leveling required

Finishes

Standard and custom options available

- Anodized, veneer-wrapped, and powder-coated aluminum
- Specialty metal finishes

Standard Joints

- Polycarbonate extrusions or 3M Dual Lock upon request

Construction

- Architectural grade aluminum alloys
- Blocking required where system meets drywall

Accessibility

- ADA compliant door clearances, surfaces, and hardware

Acoustics

- All profiles come with acoustic gaskets
- Sound transmission class varies: single glazed STC 36-41; dual glazed STC 43-49

Sustainability

We care about the environment. Our products are engineered to minimize impact and maximize performance, with supporting certifications and transparency labels.