

Our state-of-the-art telescopic wall system is a slim, elegant solution for spaces where versatility is required. Expertly engineered telescoping panels open and close effortlessly.

Product Features

- · Incredibly slim panels that can span wide openings
- · Quickly transform a space from open to closed to open again
- · Top hung with an integrated, retractable wheel in our frame
- · No floor track required
- · Glazing 1/2" and 1/4" monolithic, tempered
- · Maximum panel height 10'-0"
- · Locking or non-locking pulls
- · Multiple design options available (including applied mouldings)
- · Easily integrates with panic doors when required

Finishes

Available in all 20 standard Modernus aluminum finishes, integrating perfectly with our LAMA Glass Walls for easy coordination between systems.

Construction

- · Blocking required where system meets drywall
- · Opening must be plumb and level within $\pm \frac{1}{8}$ " across entire opening
- Maximum door weight is 220 lb per sliding door.
 Header must be able to support all doors when in open position
- · Telescopic system must be centered on header
- · Finished floor needs to be a hard surface

Accessibility

TELO meets most requirements for ADA, egress, and opening sizes. Project-specific solutions may also be developed on a project-by-project basis with our Strategic Solutions Managers.

Sustainability

We care about the environment. Our products are engineered to minimize impact and maximize performance, with supporting certifications and transparency labels.