

TELO

SYSTEM OVERVIEW



Our state-of-the-art telescopic wall system is a slim, elegant solution for spaces where versatility is required. Expertly engineered telescoping panels open and close effortlessly.

Product Features

- Incredibly slim panels that can span wide openings
- Quickly transform a space from open to closed to open again
- Top hung with an integrated, retractable wheel in our frame
- No floor track required
- Glazing ½" and ¾" monolithic, tempered
- Maximum panel height 10'-0"
- Locking or non-locking pulls
- Multiple design options available (including applied mouldings)
- Easily integrates with panic doors when required

Finishes

Available in all 19 standard Modernus aluminum finishes, integrating perfectly with our LAMA Glass Walls for easy coordination between systems.

Construction

- Blocking required where system meets drywall
- Opening must be plumb and level within +/- ¼" across entire opening
- Maximum door weight is 220 lb per sliding door. Header must be able to support all doors when in open position
- Telescopic system must be centered on header

Accessibility

TELO meets most requirements for ADA, egress, and opening sizes. Project-specific solutions may also be developed on a project-by-project basis with our Strategic Solutions Managers.

Sustainability

We care about the environment, and our products are designed and engineered to minimize impact and maximize performance. To learn more, contact your Strategic Solutions Manager.